

Foil Faced Rockfibre Slab MP573 & MP574

Technical Data Sheet

Foil Faced Rockfibre Slab MP573 & MP574 is designed for use in thermal and acoustic applications where a high efficiency vapour barrier IS REQUIRED.

PRODUCT

Foil Faced Rockfibre Slab MP573 & MP574 is manufactured from a non-combustible mineral fibre layer with a factory-bonded foil facing.

Intended for use within a variety of applications to provide a thermal and acoustic insulation solution.

Facings

MP573

Foil/Scrim/Kraft paper laminate vapour barrier.

MP574

Aluminium Foil/Scrim/Polythene laminate vapour barrier.

Fixing detail is dependent upon the intended application. In most circumstances the foil facing is placed on the warm side of the structure.



Foil Faced Rockfibre Slab MP573 & MP574.

SPECIFICATION

- High efficiency vapour barrier
- Wide range of densities available
- Easy to install

Thickness: 25, 30, 40, 50, 60, 75, 100mm

Slab Size: 600 x 1200mm

Densities: 33, 45, 60, 80 & 100kg/m³

Other thicknesses, sizes and densities are available to order.

PRODUCT PERFORMANCE

THERMAL CONDUCTIVITY	
33kg/m ³	0.037 W/mK
45kg/m ³ – 140kg/m ³	0.035 W/mK